



SPEZIFIKATIONEN

RAHMEN & GABEL	
RAHMENGRÖSSEN	S, M, L, XL
FARBE	Metallblack-Vibrantblue Matt / Metallicorange-Black
RAHMEN	GIANT Trance 27.5" AluX SL Aluminium, 140mm Maestro, Advanced Forged Composite Rocker Arms, OverDrive Steuerrohr, PowerCore BB92-PressFit Tretlagergehäuse, ISCG05-kompatibel, interne Zugverlegung, integrierter Kettenstreben-Protector, Boost 12x148
GABEL	FOX Performance 36 Float 27.5" 150, Grip, 3-Pos Lever, 1 1/8"-1 1/2"-OverDrive Alu-Schaft, Boost 15x110 QR, 44mm Rake
DÄMPFER	FOX Performance Float DPS, 3-Pos Lever, Metric Trunnion
COCKPIT	
LENKER	GIANT Contact TR RiserBar, 20mm Rise, 35.0x780
VORBAU	GIANT Contact SL, 8°, 35.0
SATTELSTÜTZE	GIANT Contact Switch Remote, Vario-Stütze, Zero-Offset, 30.9, 345mm/100mm (S), 395mm/125mm (M), 440mm/150mm (L-XL)
SATTEL	GIANT Contact SL Neutral, UniClip, Dynamic Cycling Fit, ParticleFlow
PEDALE	N/A
SCHALTUNG, ANTRIEB & BREMSEN	
SCHALTHEBEL	Shimano Deore XT Dyna-Sys11 M8000-I I-specII 2x11
UMWERFER	Shimano Deore XT Dyna-Sys11 M8025 DirectMount
SCHALTWERK	Shimano Deore XT Dyna-Sys11 Shadow Plus M8000
BREMSEN	Shimano Deore XT M8000, Hydraulik-Scheibenbremse, RT86 Ice-Tech Rotoren (180mm)
BREMSHEBEL	Shimano Deore XT M8000 I-specII
KASSETTE	Shimano SLX Dyna-Sys11 M7000-11f., 11-42 Z.
KETTE	KMC X11EL-1
KURBELSATZ	Shimano Deore XT Dyna-Sys11 M8000-B2 HollowTech II, 36-26 Z., MRP 2x Kettenführung
LAUFRÄDER	
TRETLAGER	Shimano BB-MT500-PA (Deore-Serie) PressFit BB92
FELGEN	GIANT AM Disc Laufrad-Satz, ETRTO 30-584
NABEN (V/H)	GIANT by Formula Performance Boost 15x110-/12x148-Steckachse
SPEICHEN	Sapim Leader 2.0 schwarz, 28/28 Speichen
REIFEN	Maxxis High Roller II, 3C MaxxTerra Triple Compound, EXO Protection, 60 TPI, faltbar, schlauchlos, 63-584 / 61-584
ZUBEHÖR	Kettenstreben-Protector, Schlauchlos-Kit, Reflektoren, Glocke

PRODUKTMERKMALE

- Rahmen: GIANT Trance 27.5" AluX SL Aluminium, 140mm Maestro, Advanced Forged Composite Rocker Arms, OverDrive Steuerrohr, PowerCore BB92-PressFit Tretlagergehäuse, ISCG05-kompatibel, interne Zugverlegung, integrierter Kettenstreben-Protector, Boost 12x148
- Gabel: FOX Performance 36 Float 27.5" 150, Grip, 3-Pos Lever, 1 1/8"-1 1/2"-OverDrive Alu-Schaft, Boost 15x110 QR, 44mm Rake
- Schalthebel: Shimano Deore XT Dyna-Sys11 M8000-I I-specII 2x11
- Kurbelsatz: Shimano Deore XT Dyna-Sys11 M8000-B2 HollowTech II, 36-26 Z., MRP 2x Kettenführung
- Farbe: Metallblack-Vibrantblue Matt / Metallicorange-Black

UVP: 2.799,90 €

GEOMETRIEDATEN

RAHMEN & GABEL	S	M	L	XL
Sitzrohrlänge (mm)	380	431	482	507
Sitzwinkel	73,5°	73,5°	73,5°	73,5°
Oberrohrlänge (mm)	580	610	630	655
Steuerrohrlänge (mm)	100	105	130	145
Lenkwinkel	67,0°	67,0°	67,0°	67,0°
Gabelvorbiegung (mm)	42	42	42	42
Gabelnachlauf (mm)	104	104	104	104
Radstand (mm)	1129	1160	1183	1209
Kettenstrebenlänge (mm)	435	435	435	435
Tretlagerabsenkung (mm)	15	15	15	15
Stack (mm)	587	591	614	628
Reach (mm)	406	435	448	469
Überstands-/Durchstiegshöhe (mm)	701	723	768	788
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	50	50	50	60
Kurbelarmlänge (mm)	170	175	175	175
Raddurchmesser	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbänderungen vorbehalten.