



## SPEZIFIKATIONEN

RAHMEN & GABEL	
RAHMENGRÖSSEN	XS, S, M, L
FARBE	White
RAHMEN	Liv Pique 27.5" AluX SL Aluminium, 120mm Maestro, Advanced Forged Composite Rocker Arms, OverDrive Steuerrohr, PowerCore BB92-PressFit Tretlagergehäuse, interne Zugverlegung, integrierter Kettenstreben-Protector, Boost 12x148
GABEL	FOX Rhythm 34 Float EVOL 27.5" 130, Grip, 2-Pos Remote, 1 1/8"-1 1/2"-OverDrive Alu-Schaft, Boost 15x110 QR, 44mm Rake
DÄMPFER	FOX Performance Float DPS, LV EVOL, 3-Pos Lever, Metric Trunnion
COCKPIT	
LENKER	GIANT Connect TR RiserBar, 20mm Rise, 5° up / 7° back, 31.8
VORBAU	GIANT Connect, 8°, 31.8
SATTELSTÜTZE	GIANT Contact Switch-Remote, Vario-Stütze, Zero-Offset, 30.9, 345mm/100mm (XS-M), 395mm/125mm (L)
SATTEL	Liv Contact Forward
SCHALTUNG, ANTRIEB & BREMSEN	
SCHALTHEBEL	Shimano SLX Dyna-Sys11 M7000-I I-specII 2x11
UMWERFER	Shimano SLX Dyna-Sys11 M7025 DirectMount
SCHALTWERK	Shimano Deore XT Dyna-Sys11 Shadow Plus M8000
BREMSEN	Shimano MT500 (Deore-Serie), Hydraulik-Scheibenbremse, RT56-Rotoren (180mm)
BREMSHEBEL	Shimano MT500 I-specII (Deore-Serie)
KASSETTE	Shimano SLX Dyna-Sys11 M7000-11f., 11-42 Z.
KETTE	KMC X11EL-1
KURBELSATZ	Shimano SLX Dyna-Sys11 M7000-2 HollowTech II, 34-24 Z.
LAUFRÄDER	
TRETLAGER	Shimano BB-MT500-PA (Deore-Serie) PressFit BB92
FELGEN	GIANT XC 1 Disc Laufrad-Satz, ETRTO 23-584
NABEN (V/H)	GIANT by Formula Tracker Boost 15x110 / 12x148-Steckachse
SPEICHEN	Sapim Race 2.0-1.8 schwarz, 28/28 Speichen
REIFEN	Maxxis Forekaster, EXO Protection, Dual Compound, faltbar, schlauchlos, 60 TPI, 60-584 / 120 TPI, 56-584
ZUBEHÖR	Kettenstreben-Protector, Tubeless-Kit, Reflektoren, Glocke

## PRODUKTMERKMALE

- ALUXX SL-grade Aluminium frame with 120mm Maestro suspension
- Fox 34 Rhythm, 130mm fork with remote lockout
- Fox Float Performance trunnion mount shock
- Shimano SLX/XT 2x11 speed drivetrain
- Giant Contact Switch Trail dropper seatpost
- Shimano hydraulic disc brakes
- Color: White/Black/Rainbow



UVP: 2.499,90 €

## GEOMETRIEDATEN

RAHMEN & GABEL	XS	S	M	L
Sitzrohrlänge (mm)	345	390	440	490
Sitzwinkel	73,0°	72,5°	72,5°	72,5°
Oberrohrlänge (mm)	552	572	592	602
Steuerrohrlänge (mm)	95	100	110	120
Lenkwinkel	69,4°	69,4°	69,4°	69,4°
Gabelvorbiegung (mm)	42	42	42	42
Gabelnachlauf (mm)	88	88	88	88
Radstand (mm)	1058	1073	1094	1104
Kettenstrebenlänge (mm)	430	430	430	430
Tretlagerabsenkung (mm)	21	21	21	21
Stack (mm)	581	586	595	605
Reach (mm)	374	387	404	411
Überstands-/Durchstiegshöhe (mm)	661	692	725	761
Lenkerbreite (mm)	750	750	780	780
Vorbaulänge (mm)	40	50	50	60
Kurbelarmlänge (mm)	170	170	170	175
Raddurchmesser	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbänderungen vorbehalten.